


## Features

- 7dBm Output Level at 381.19 MHz
- Channel Step Size:10 kHz
- 2<sup>nd</sup> Harmonic: <-20 -dBc
- Spurious Level: < -65dBc
- Lock Time : <10ms
- 35mA Current Consumption

## Description

The plerow™ PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



## Specifications

Parameter	Unit	Min.	Typical	Max.
Frequency Range	MHz		381.19	
Output Power	dBm	5	7	
Supply Voltage	V	4.75	5	5.25
Current Consumption	mA		25	35
Channel Step Size	kHz		10	
2 <sup>nd</sup> Harmonics	dBc		-25	-20
Spurious Level	dBc		-70	-65
Lock Time			3	10
Reference Frequency	MHz		13	
Reference Input Level	dBm		-	
Phase Noise (C / N)				
@ 1 kHz			-80	-75
@ 10 kHz	dBc/Hz		-106	-102
@ 100 kHz			-120	-115
Output Impedance	Ω		50	
Operating Temp. Range	°C	-40	25	80
Package Type & Size	mm	SMT, 19.0W×19.0L×5.8H		

1) Measurement conditions are as follows: T = 25°C, V<sub>CC</sub> = 5 V, Freq. = 562.75MHz, 50 ohm system.

2) Frequency stability of internal ref. TCXO is +/- 2.5 ppm (max.) over the operating temperature range.

## More Information

Website: [www.asb.co.kr](http://www.asb.co.kr)  
E-mail: [sales@asb.co.kr](mailto:sales@asb.co.kr)


Tel: (82) 42-528-7220  
Fax: (82) 42-528-7222

ASB Inc., 4th Fl. Venture Town  
Bldg., 367-17 Goijeong-Dong, Seo-  
Gu, Daejeon 302-716, Korea

Outline Drawing

APL0000-R/T Type

Type	Dimension
PLL IC + VCO + ROM + TCXO	19 x 19 x 5.8



Pin Out for PLL			
Pin No.	Application	Pin No.	Application
1	GROUND	9	VCC (VCO)
2	GROUND	13	RF OUT
3	GROUND	15	VCC (PLL)
4	GROUND	16	LOCK DETECT
All other Pins are Grounded / Internal TCXO and ROM			

