


Features

- 0 dBm Output Level at 1515.42 MHz
- Channel Step Size : 500 kHz
- 2nd Harmonic: < -30 dBc
- Spurious Level: < -75 dBc
- Lock Time : < 5 ms
- 40 mA Current Consumption

Description

The plerow™ PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



Specifications

Parameter	Unit	Min.	Typical	Max.
Frequency Range	MHz		1515.42	
Output Power	dBm	-1	0	1
Supply Voltage	V	4.7	5	5.3
Current Consumption	mA		25	40
2 nd Harmonics	dBc		500	
Spurious Level	dBc		-25	-30
Lock Time	ms			-75
Reference Frequency	MHz		3	5
Reference Input Level	dBm		10	
Phase Noise (C / N)		1	3	5
@ 10 kHz			-103	-108
@ 100 kHz	dBc/Hz		-115	-120
@ 1 MHz			-125	-130
Output Impedance	Ω		50	
Operating Temp. Range	°C	-40	25	80
Package Type & Size	mm	SMT, 19.0W×19.0L×5.8H		

1) Measurement conditions are as follows: T = 25°C, V_{CC} = 5 V, Freq. = 1515.42 MHz, 50 ohm system.

More Information

Website: www.asb.co.kr
E-mail: sales@asb.co.kr


Tel: (82) 42-528-7220
Fax: (82) 42-528-7222

ASB Inc., 4th Fl. Venture Town
Bldg., 367-17 Goijeong-Dong,
Seo-Gu, Daejeon 302-716, Ko-
rea

Outline Drawing

APL0000-R Type

Type	Dimension
PLL IC + VCO + ROM	19 x 19 x 5.8



Pin Out for PLL			
Pin No.	Application	Pin No.	Application
1	GROUND	9	VCC (VCO)
2	GROUND	13	RF OUT
3	GROUND	15	VCC (PLL)
4	OSC IN	16	LOCK DETECT
All other Pins are Grounded / Internal ROM			

