


Features

- +10 dBm Output Level at 2062.50 MHz
- 2nd Harmonic: < -20dBc
- Spurious Level : < -70 dBc
- Lock Time : < 10ms
- 50mA Current Consumption
- Strip-line Resonator

Description

The plerow™ PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



Specifications

Parameter	Unit	Min.	Typical	Max.
Frequency Range	MHz		2062.5	
Output Power	dBm	+8	+10	+12
Supply Voltage	V	4.75	5.00	5.25
Current Consumption	mA			50
Channel Step Size	kHz		-	
2 Harmonics (Fundamental)	dBc		-20	
Spurious Level	dBc		-70	
Lock Time	ms		3	10
Reference Frequency	MHz		-	
Reference Input Level	dBm		-	
Phase Noise (C / N)				
@ 1 kHz	dBc/Hz		-73	
@ 10kHz			-100	
@ 100 kHz			-118	
Output Impedance	Ω		50	
Operating Temp. Range	°C	-40	+25	+85
Package Type & Size	mm	SMT, 19.0W×19.0L×5.8H		

1) Measurement conditions are as follows: T = 25°C, V_{CC} = 5 V, Freq. = 2062.5 MHz, 50 ohm system.

More Information

Website: www.asb.co.kr
E-mail: sales@asb.co.kr


Tel: (82) 42-528-7220
Fax: (82) 42-528-7222

ASB Inc., 4th Fl. Venture Town
Bldg., 367-17 Goijeong-Dong,
Seo-Gu, Daejeon 302-716, Korea

Outline Drawing

APL0000-R/T Type

Type	Dimension
PLL IC + VCO + ROM + TCXO	19 x 19 x 5.8



Pin Out for PLL			
Pin No.	Application	Pin No.	Application
1	GROUND	9	VCC (VCO)
2	GROUND	13	RF OUT
3	GROUND	15	VCC (PLL)
4	GROUND	16	LOCK DETECT
All other Pins are Grounded / Internal TCXO and ROM			

